



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product Identifier

5-140 Easy Fill Bodyfiller

#### 1.3. Details of the supplier of the safety data sheet

COMPANY IDENTITY: Logicar Inc.  
COMPANY ADDRESS: 1361 NW 155<sup>th</sup> DR  
COMPANY CITY: Miami, FL 33169  
COMPANY PHONE: 305-685-8044

#### 1.4. Emergency telephone number

CHEMTREC (800) 424-9300

### Section 2: Hazards identification

#### Hazard(s) identification

**Physical hazards** Flammable liquids Category 3

**Health hazards** Acute toxicity, oral Category 4

Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Germ cell mutagenicity Category 1B

Carcinogenicity Category 1B

Reproductive toxicity Category 1

Specific target organ toxicity, repeated Category 1

exposure

Hazardous to the aquatic environment, acute Category 2

hazard

#### Environmental hazards

Hazardous to the aquatic environment, Category 2

long-term hazard

**OSHA defined hazards** Not classified.

#### 2.2. Label elements



**Signal word** Danger



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

**Hazard statement** Flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

### Precautionary statement

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling.

Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

**Storage** Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

**Supplemental information** 76.09% of the mixture consists of component(s) of unknown acute oral toxicity. 83.05% of the mixture consists of component(s) of unknown acute inhalation toxicity. 78.52% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 78.52% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

### Section 3: Composition/information on ingredients

#### 3.1. Mixtures

Chemical name	CAS number	%
Calcium carbonate	1317-65-3	30 to <40
Styrene, monomer	100-42-5	10 to <20
Talc	14807-96-6	5 to <10
Magnesium carbonate	546-93-0	1 to <5
Silicon dioxide	7631-86-9	1 to <5
Sodium silicate	1344-09-8	1 to <5
dist. cat. reformer residue	68477-30-5	0.1 to <1
heavy aromatic naphtha	64742-94-5	0.1 to <1
Sodium metaborate	7775-19-1	0.1 to <1
Titanium dioxide	13463-67-7	0.1 to <1



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

### Section 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
----------------------------	--

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

### 5.3. Advice for fire-fighters

#### Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

#### Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

#### Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

#### General fire hazards

Flammable liquid and vapor.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

### 6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

**Large Spills:** Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Prevent product from entering drains. Following product recovery, flush area with water.



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

**Small Spills:** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

#### 7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m <sup>3</sup> 15 mg/m <sup>3</sup>	Respirable fraction. Total dust.
heavy aromatic naphtha (CAS 64742-94-5)	PEL	400 mg/m <sup>3</sup> 100 ppm	



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

Magnesium carbonate (CAS 546-93-0) PEL 5 mg/m<sup>3</sup> Respirable fraction.

Titanium dioxide (CAS 13463-67-7) PEL 15 mg/m<sup>3</sup> Total dust.  
15 mg/m<sup>3</sup> Total dust.

### US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Styrene, monomer (CAS 100-42-5)	Ceiling	200 ppm
	TWA	100 ppm

### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Silicon dioxide (CAS 7631-86-9)	TWA	0.8 mg/m <sup>3</sup> 20 mppcf	
Talc (CAS 14807-96-6)	TWA	0.3 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> 20 mppcf 2.4 mppcf	Total dust. Respirable. Respirable.

### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
heavy aromatic naphtha (CAS 64742-94-5)	TWA	200 mg/m <sup>3</sup>	Non-aerosol.
Styrene, monomer (CAS 100-42-5)	STEL	40 ppm	
	TWA	20 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m <sup>3</sup>	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m <sup>3</sup>	

### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m <sup>3</sup>	Respirable.
Magnesium carbonate (CAS 546-93-0)	TWA	10 mg/m <sup>3</sup> 5 mg/m <sup>3</sup>	Total Respirable.
Silicon dioxide (CAS 7631-86-9)	TWA	10 mg/m <sup>3</sup> 6 mg/m <sup>3</sup>	Total
Styrene, monomer (CAS 100-42-5)	STEL	425 mg/m <sup>3</sup>	
	TWA	100 ppm 215 mg/m <sup>3</sup> 50 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m <sup>3</sup>	Respirable.

### Biological limit values

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling	Time
Styrene, monomer (CAS 100-42-5)	400 mg/g	Mandelic acid Plus phenylglyoxylic acid	Creatinine in urine	*	
	0.2 mg/l	Styrene	Venous blood	*	



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

### 8.2. Exposure controls

#### Exposure guidelines

##### US - California OELs: Skin designation

Styrene, monomer (CAS 100-42-5)

Can be absorbed through the skin.

##### US - Minnesota Haz Subs: Skin designation applies

Styrene, monomer (CAS 100-42-5)

Skin designation applies.

##### US ACGIH Threshold Limit Values: Skin designation

heavy aromatic naphtha (CAS 64742-94-5)

Can be absorbed through the skin.

#### Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear safety glasses with side shields (or goggles).

##### Skin protection

##### Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

##### Other

Wear appropriate chemical resistant clothing.

##### Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

##### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

#### General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

##### Physical state

Liquid.

##### Form

Liquid. Paste

##### Color

Not available.

##### Odor

Not available.

##### Odor threshold

Not available.

##### pH

Not available.

##### Melting point/freezing point

-23.8 °F (-31 °C) estimated

##### Initial boiling point and boiling range

293 °F (145 °C) estimated

##### Flash point

93.9 °F (34.4 °C) estimated



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1.1 % estimated
<b>Flammability limit - upper (%)</b>	6.1 % estimated
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	5.68 hPa estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	914 °F (490 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	9.70 lbs/gal
<b>Flammability class</b>	Flammable IC estimated
<b>Percent volatile</b>	16.92 % estimated
<b>Specific gravity</b>	1.17
<b>VOC</b>	16.6395 % estimated

### Section 10: Stability and reactivity

#### 10.1. Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Material is stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

### 10.4. Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

### 10.5. Incompatible materials

Strong acids. Aluminum. Peroxides. Fluorine.

### 10.6. Hazardous decomposition products

No hazardous decomposition products are known.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	Harmful if inhaled. Harmful if swallowed.	
Components	Species	Test Results
heavy aromatic naphtha (CAS 64742-94-5)		
<u>Acute</u>		
<u>Inhalation</u>		
LC50	Rat	61 mg/l, 4 Hours
<u>Oral</u>		
LD50	Rat	> 25 ml/kg
Silicon dioxide (CAS 7631-86-9)		
<u>Acute</u>		
<u>Oral</u>		
LD50	Mouse	> 15000 mg/kg
	Rat	> 22500 mg/kg
Sodium metaborate (CAS 7775-19-1)		
<u>Acute</u>		
<u>Oral</u>		
LD50	Rat	2330 mg/kg
Sodium silicate (CAS 1344-09-8)		
<u>Acute</u>		
<u>Oral</u>		
LD50	Mouse	1100 mg/kg
	Rat	1.1 g/kg
Styrene, monomer (CAS 100-42-5)		
<u>Acute</u>		
<u>Inhalation</u>		
LC50	Mouse	4940 ppm, 2 Hours
	Rat	2770 ppm, 4 Hours
		24 mg/l, 4 Hours
<u>Oral</u>		
LD50	Mouse	316 mg/kg
	Rat	1 g/kg

\* Estimates for product may be based on additional component data not shown.



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

**Skin corrosion/irritation**  
**Serious eye damage/eye irritation**

Causes skin irritation.  
Causes serious eye irritation.

**Respiratory or skin sensitization**  
**Respiratory sensitization**  
**Skin sensitization**  
**Germ cell mutagenicity**  
**Carcinogenicity**

Not a respiratory sensitizer.  
This product is not expected to cause skin sensitization.  
May cause genetic defects.  
May cause cancer.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Silicon dioxide (CAS 7631-86-9) 3  
Styrene, monomer (CAS 100-42-5) 2B  
Titanium dioxide (CAS 13463-67-7) 2B

Not classifiable as to carcinogenicity to humans.  
Possibly carcinogenic to humans.  
Possibly carcinogenic to humans.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### US. National Toxicology Program (NTP) Report on Carcinogens

Styrene, monomer (CAS 100-42-5)

Reasonably Anticipated to be a Human Carcinogen.

**Reproductive toxicity**  
**Specific target organ toxicity - single exposure**  
**Specific target organ toxicity - repeated exposure**  
**Aspiration hazard**  
**Chronic effects**

May damage fertility or the unborn child.  
Not classified.  
Causes damage to organs through prolonged or repeated exposure.  
Not an aspiration hazard.  
Causes damage to organs through prolonged or repeated exposure.  
Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## Symptoms / routes of exposure

### Information on likely routes of exposure

**Inhalation** Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation.  
**Skin contact** Causes skin irritation.  
**Eye contact** Causes serious eye irritation.  
**Ingestion** Harmful if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation. May cause redness and pain.



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

### Section 12: Ecological information

#### 12.1. Toxicity

Ecotoxicity	Toxic to aquatic life with long lasting effects.		
Components	Species	Test Results	
heavy aromatic naphtha (CAS 64742-94-5)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
Sodium silicate (CAS 1344-09-8)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	0.28 - 0.57 mg/l, 48 hours
Fish	LC50	Western mosquitofish (Gambusia affinis)	1800 mg/l, 96 hours
Styrene, monomer (CAS 100-42-5)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	3.3 - 7.4 mg/l, 48 hours
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	5.1 - 16 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

#### 12.3. Bioaccumulative potential

##### Partition coefficient n-octanol / water (log Kow)

Styrene, monomer 2.95

#### 12.6. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products**

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### Section 14: Transport information

#### 14.1. UN number

UN 1866

#### 14.2. UN proper shipping name

Resin Solution

#### 14.3. Transport hazard class(es)

Class 3

#### 14.4. Packing group

PG III

#### 14.5. Environmental hazards

Marine pollutant No.

#### 14.6. Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

### Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**



# Safety Data Sheet

## 5-140 Easy Fill Bodyfiller

Styrene, monomer (CAS 100-42-5) Listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous chemical

No

### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Styrene, monomer	100-42-5	10 to <20

## Section 16: Other information

### Other information

Issue date	03-20-2015
Version #	01
HMIS® ratings	Health: 2* Flammability: 3 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 3 Instability: 0