



# Safety Data Sheet

## 30-72 NORMAL HARDENER

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product Identifier

30-72 NORMAL HARDENER  
Contains: Methyl acetate  
EUH204 Contains isocyanates. May produce an allergic reaction

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Hardener normal for clear coat 82-50 for car bodies

#### 1.3. Details of the supplier of the safety data sheet

COMPANY IDENTITY: Logicar Inc.  
COMPANY ADDRESS: 1361 NW 155<sup>th</sup> DR  
COMPANY CITY: Miami, FL 33169  
COMPANY PHONE: 305-685-8044

#### 1.4. Emergency telephone number

CHEMTREC: +1(703)527-3887

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Flam. Liq. 2 H225  
Acute Tox. 4 H312  
Skin Irrit. 2 H315  
Skin Sens. 1 H317  
Eye Irrit. 2 H319  
Acute Tox. 4 H332  
STOT SE 3 H335  
STOT SE 3 H336

#### 2.2. Label elements



Signal word : DANGER



# Safety Data Sheet

## 30-72 NORMAL HARDENER

**Hazard statements:**

- H225 Very flammable liquid and vapour
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking

**Precautionary statements:**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P260 Do not breathe vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing..
- P501 Dispose of contents/container to an authorized waste collection point.
- 2.3 Other hazards – no available

### Section 3: Composition/information on ingredients

#### 3.1. Mixtures

Index number	Chemical Name	WE Number	CAS Number	Classification of substance according to CLP	Mark of substance	Weight	Registration Number
-	1,6-Hexamethylene diisocyanate dimer; homopolymer	500-060-2	28182-81-2	Skin Sens. 1 H317 Acute Tox. 4 H332 STOT SE 3 H335	GHS07 Wng H317, H332, H335	25 – 35%	01- 2119485796- 17-0000
607-021-00-X	Methyl acetate	201-185-2	79-20-9	Flam Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336	GHS02 GHS07 Dgr H225 H319 H336 EUH066	25 – 35%	17- 2120049057- 58-0000
607-195-00-7	1-methoxy-2-propyl acetate	203-603-9	108-65-6	Flam. Liq. 3, H226 Eye Irrit. 2, H319	GHS02 GHS07 Wng H226, H319	10 – 15%	01- 2119475791- 29-XXXX
601-022-00-9	Xylene	215-535-7	1330-20-7	Flam. Liq. 3 H226 Acute Tox. 4 * H332 Acute Tox. 4 * H312 Skin Irrit. 2 H315	GHS02 GHS07 Wng H226, H332 H312, H315	5 – 11%	01- 2119488216- 32-XXXX
607-025-00-1	Butyl acetate	204-658-1	123-86-4	Flam. Liq. 3 H226 STOT SE 3 H336	GHS02 GHS07 Wng H226, H336, EUH066	5 – 10%	01- 2119485493- 29-XXXX
-	3-ethoxypropionate	212-112-9	763-69-9	Flam. Liq. 3 H226 EUH066	GHS02 Wng H226 EUH066	5 – 10%	01- 2119463267- 34-XXXX



# Safety Data Sheet

## 30-72 NORMAL HARDENER

### Section 4: First aid measures

#### 4.1. Description of first aid measures

General information: See 11 point SDS  
Inhalation: Move to fresh air, ensure quiet and warmth, seek medical advice.  
Eyes contact: Do not close the eye, rinse with plenty of water (protect) healthy eye, remove contact lenses, seek medical advice.  
Skin contact: Immediately remove all contaminated clothing, wash with plenty of water with soap, seek medical advice.  
Ingestion: Wash out mouth thoroughly with water. Drink 2-4 glasses of water. Do not induce the vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

Seek medical advice

#### 4.3. Indication of any immediate medical attention and special treatment needed

Seek medical advice

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Water, vaporised water, foam, CO<sub>2</sub>.  
Unsuitable extinguishing media: Tight stream of water.

#### 5.2. Special hazards arising from the substance or mixture

Under the influence of high temperature may produce CO, CO<sub>2</sub>, and isocyanate vapours.

#### 5.3. Advice for fire-fighters

Firemen have to wear self-contained breathing apparatus and protective clothing. Cool adjacent tanks by spraying water from a safe distance

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Remove ignition sources. Provide for sufficient ventilation. Avoid direct contact with releasing substance (vapours). Avoid contact with eyes and skin. Get acquainted with safety conditions (see point 7 and 8 SDS).  
For emergency responders



# Safety Data Sheet

## 30-72 NORMAL HARDENER

### 6.2. Environmental precautions

Keep away from drains, surface-water, ground-water and soil

### 6.3. Methods and material for containment and cleaning up

Poured substance should be absorbed with non-flammable materials : sand, silica, special granulated products. Keep to a minimum efflux area. Collect discards, store according to regulations (see point 13 SDS).

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat; keep away from sources of ignition – do not smoke, do not eat, do not drink, do not breathe vapour, avoid contact with skin and eyes. Do not empty under pressure. Use only original tanks.

### 7.2. Conditions for safe storage, including any incompatibilities

Normal precautions taken when handling flammable substances. Store in hermetically closed containers In temp. 5-25°C. Place of storage should be dry. Protect from heat. Do not store near to sources of ignition.

### 7.3. Specific end use(s)

Hardener normal for clear coat 82-50 for car bodies

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

Limit values for Xylene

TLV: 100 ppm as TWA 150 ppm as STEL A4 (ACGIH 2001).  
BEI (ACGIH 2001).

EU Limit Values: 50 ppm 221 mg/m<sup>3</sup> (8 hours)

100 ppm 442 mg/m<sup>3</sup> (short-term) skin

Limit values for Butyl acetate:

TLV: 150 ppm as TWA 200 ppm as STEL (ACGIH 2003).

MAK: 100 ppm 480 mg/m<sup>3</sup>

Limit values for 1-methoxy-2-propyl acetate acetate:

TLV: 100 ppm; 369 mg/m<sup>3</sup> (as TWA), 150 ppm; 553 mg/m<sup>3</sup> (STEL) (ACGIH 1997).

EU OEL: 100 ppm 375 mg/m<sup>3</sup> as TWA 150 ppm 568 mg/m<sup>3</sup> as STEL (skin) (EU 2000).

EU Limit Values: 50 ppm 275 mg/m<sup>3</sup> (8 hours)

100 ppm 550 mg/m<sup>3</sup> (short-term) skin



# Safety Data Sheet

## 30-72 NORMAL HARDENER

### 8.2. Exposure controls

Respiratory protection:	Gas mask with "A" type absorbing canister.
Hands protection:	Protective gloves for handling solvents (nitrile rubber).
Eyes protection:	Protective glasses.
Skin protection:	Suitable protective clothing.
Workplace:	Topical stays and exhausting ventilation.

### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	liquid	Autoignition point:	no data
Colour:	colourless	Vapour pressure:	no data
Odour:	typical mixture of solvents	Explosion limits:	no data
pH:	no data	Density:	0,976 g/cm <sup>3</sup>
Boiling point:	> 56°C	Water solubility:	very poor
Melting point:	no data	Octanol/Water partition coeff:	no data
Flash point:	<0°C	Viscosity:	no data

### Section 10: Stability and reactivity

#### 10.2. Chemical stability

If handled according to the section 7 product is stable

#### 10.5. Incompatible materials

Strong acids and basis, high temperature, fire

#### 10.6. Hazardous decomposition products

Incomplete combustion will produce CO, CO<sub>2</sub> and toxic gases

### Section 11: Toxicological information

#### 11.1. Information on toxicological effects

Toxicity for Xylene:	LD50 (rat, oral) – 4300 mg/kg LC50 (rat, inhalation) – 22100 mg/m <sup>3</sup> (4 h) LD50 (rabbit, rat, skin) – no data
Toxicity for 1-methoxy-2-propyl acetate:	LD50 (rat, oral) – 8532 mg/kg LD50 (rat, skin) – 5000 mg/kg



# Safety Data Sheet

## 30-72 NORMAL HARDENER

Toxicity for Butyl acetate:	LD50 (rat, oral) – 6400 mg/kg LC50 (rat, inhalation) – 9,6 mg/l (4h) LD50 (rabbit, skin) – >5000 mg/kg
Toxicity for Methyl acetate:	LD50 (rat, oral) – 5000 mg/kg LD50 (rat, skin) – 2000 mg/kg LC50 (rat, inhalation) > 49mg/l (4h)
Irritating effect:	Skin: prolonged or repeated exposure may result in drying of the epidermis, loss of the protective fat layer and permeation of the harmful substances to the subcutaneous layer. Eyes: irritation of the mucosa and irreversible changes in the eye.

### Symptoms / routes of exposure

Headaches, tiredness, muscle failure, partial or total loss of consciousness

## Section 12: Ecological information

### 12.1. Toxicity

Xylene acute toxicity for:	(LC50/96 h) fish – 13500 - 17300 mg/l (LC50//48h) crustacea – 600 mg/l
1-methoxy-2-propyl acetate acetate acute toxicity for:	(LC50/96 h) fish > 161 mg/l (EC50//48h) crustacea > 500 mg/l
Methyl acetate acute toxicity for:	(LC50/96 h) fish –320 mg/l (EC50//48h) crustacea – 1026,7 mg/l
Butyl acetate acute toxicity for:	(LC50/96 h) fish – 18 mg/l (EC50//48h) crustacea – 32 mg/l

### 12.6. Other adverse effects

The product is very poorly soluble in water. Do not allow to enter the sewage system, soil, or water reservoirs – inform the local authorities.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

Recommendation:	Product must be disposed of by special means in accordance with local regulations.
Remains of product:	Remains of product in the tin should be carefully remove with 82-50 2:1 VOC<4.2 to harden. Harden product is not harmfully substance and could be treat like wastes in accordance with regulation
Clean tin:	Tin carefully clean is not harmful waste. Code of waste : 15 01 04 Spent packages dispose for authorized receiver who has adequate permission for waste management.
Tin partly empty:	See remains of products. Packs of an article containing residues of hazardous substances or contaminated by a hazardous waste code 15 01 10*



# Safety Data Sheet

## 30-72 NORMAL HARDENER

### Section 14: Transport information

#### 14.1. UN number

UN 1263

#### 14.2. UN proper shipping name

PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)

CLASS 3

#### 14.4. Packing group

PG II

#### 14.6. Special precautions for user

Land transport: ADR/RID:

Classification code: F1

Tunnels: D1E

Sea transport IMDG: EmS: F-E, S-E

### Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

67/548/EWG (2006/121/WE)

91/155/EWG (2001/58/WE)

1999/45/EC (2006/8/WE)

1991/322/EWG

2000/39/WE

2006/15/WE

2006/1907/WE (REACH)

2004/42/WE

209/790/WE

2008/1272/WE (CLP)



# Safety Data Sheet

## 30-72 NORMAL HARDENER

### Section 16: Other information

#### Other information

Full text of phrases from 3 point SDS according to CLP  
H225 Very flammable liquid and vapour  
H226 Flammable liquid and vapour  
H312 Harmful in contact with skin  
H315 Causes skin irritation  
H317 May cause an allergic skin reaction  
H319 Causes serious eye irritation  
H332 Harmful if inhaled  
H335 May cause respiratory irritation  
H336 May cause drowsiness or dizziness  
EUH066 Repeated exposure may cause skin dryness or cracking  
Flam. Liq. 2 Flammable liquid category 2  
Flam. Liq. 3 Flammable liquid category 3  
STOT SE 3 Specific target organ toxicity – single exposure category 3  
Acute Tox. 4\* Acute toxicity category 4  
Eye Irrit. 2 Eye irritation category 2  
Skin Irrit. 2 Skin irritation category 2  
Skin Sens. 1 Skin sensitization category 1